

PRINTING METHOD	Piezoelectric Head
PRINTER	LITE 17, LITE 70, PRO 17 y PRO 70
PRINTING SPEED	Up to 50 m/min. With encoder at 34 m/min.
PRINT RESOLUTION	Up to 360 dpi at 75 pl
MAXIMUM PRINT HEIGHT	17 mm (LITE 17, PRO 17) 70 mm (LITE 70, PRO 70)
MAXIMUM PRINT LENGTH	2000 mm
INK BOTTLE CAPACITY	500 ml
STANDARD INTERFACE	USB 2.0 (Type A), Ethernet (IPv4/v6)
POWER REQUIREMENTS	AC100V – AC240V $\pm 10\%$, 50/60 Hz, Power supply with automatic calibration
ENVIRONMENTAL CONDITIONS	5–45°C / 10–85% RH (non-condensing)
CERTIFICATIONS	CE, EPAL, GS1
WEIGHT	LITE 4.5 kg (excluding stand) / PRO 5.5 kg (excluding stand)
DIMENSIONS	LITE: 150 x 195 x 412.5 mm (Width x Height x Depth) PRO: 150 x 195 x 592 mm (Width x Height x Depth)

Standard features

USER INTERFACE	8" colour LCD touchscreen with 1280x800 resolution
PRODUCT DETECTOR	Direct reflection PNP photocell, adjustable range (other types optional)
WARNING BEACON	3-colour status indicator
ON-SCREEN DIAGNOSTICS	Information messages on screen
ON-SCREEN INFORMATION	Status, print counters, error monitor, product sensor, printer status monitor, ink level.

Optional features

WARNING BEACON	3-colour modular status indicator
FIXED SUPPORT	Adjustable from 750 to 1100 mm
SOLID SUPPORT	Attachment to existing conveyor belts
GUIDED PRODUCT SYSTEM	Protection of the product and print head
SHOCK ABSORPTION SYSTEM	Protection of the product and print head
PRODUCT DETECTOR	PNP background suppression photocell, direct reflection and adjustable range
CONTROLLER	10.1" Display Controller for 1 printer and Multi-head Controller for up to 4 heads

SMART CODING TECHNOLOGIES

Higuera st. Unit U2 9, 4c, 12006 Castellón (Spain)
+34 685 574 705
info@scodingtech.com

All brand and product names mentioned in the brochure are the property of Smart Coding Technologies.